

D E S C R I P T I O N

Land Situated Approximately 650 feet West of Mamalahoa Highway

At Kealakehe, North Kona, Island of Hawaii, Hawaii

Being the Whole of R.P. 5228,
L.C. Aw. 8608, Apana 1 to Kaahui

Beginning at a nail in concrete at the southeast corner of this parcel of land and on the northerly side of R.P. 4005, L.C. Aw. 9252, Apana 1 to Kauhai, the coordinates of said point of beginning referred to Government Survey Triangulation Station "KAILUA" being 12,908.18 feet North and 8,022.49 feet East and running by azimuths measured clockwise from True South:

Following along stonewall, along R.P. 4005, L.C. Aw. 9252, Apana 1 to Kauhai, the direct courses to points set at centerline of stonewall for the following eight (8) courses being as follows:

- | | | |
|----|-------------|-----------------------------------|
| 1. | 72° 02' | 85.30 feet to a nail in concrete; |
| 2. | 65° 11' 30" | 84.67 feet to a nail in concrete; |
| 3. | 81° 13' 30" | 70.57 feet to a nail in concrete; |
| 4. | 68° 31' 30" | 75.62 feet to a nail in concrete; |
| 5. | 73° 54' | 92.98 feet to a nail in concrete; |
| 6. | 59° 42' | 42.24 feet to a nail in concrete; |
| 7. | 73° 51' | 26.38 feet to a nail in concrete; |
| 8. | 71° 48' | 73.81 feet to a pipe in concrete; |

Thence along stonewall, along Grant 3965 to W.M. Kalaiwaa, the direct courses to points set at centerline of stonewall for the following twelve (12) courses being as follows:

- | | | |
|-----|-------------|-----------------------------------|
| 9. | 58° 32' 30" | 29.49 feet to a nail in concrete; |
| 10. | 63° 32' | 55.58 feet to a nail in concrete; |



L.C. Aw. 8608

- | | | |
|-----|-------------|-------------------------------------------------------------------------------------------------|
| 11. | 73° 04' | 39.84 feet to a nail in concrete; |
| 12. | 80° 21' | 30.97 feet to a nail in concrete; |
| 13. | 71° 20' | 24.73 feet to a nail in concrete; |
| 14. | 80° 08' | 25.36 feet to a nail in concrete; |
| 15. | 68° 57' 30" | 24.73 feet to a nail in concrete; |
| 16. | 90° 35' 30" | 38.00 feet to a nail in concrete; |
| 17. | 66° 54' 30" | 51.22 feet to a nail in concrete; |
| 18. | 78° 34' 30" | 57.81 feet to a nail in concrete; |
| 19. | 65° 54' 30" | 32.28 feet to a nail in concrete; |
| 20. | 52° 24' | 17.67 feet to a nail in concrete; |
| 21. | 150° 08' | 169.57 feet along Grant 3965 to W.M. Kalaiwaa to a nail in concrete at centerline of stonewall; |

Thence along stonewall, along Grant 3965 to W.M. Kalaiwaa, the direct courses to points set at centerline of stonewall for the following nine (9) courses being as follows:

- | | | |
|-----|--------------|----------------------------------------------------------------------------------------------------------------------|
| 22. | 246° 51' | 13.78 feet to a nail in concrete; |
| 23. | 249° 00' | 61.20 feet to a nail in concrete; |
| 24. | 250° 42' 30" | 40.52 feet to a nail in concrete; |
| 25. | 250° 02' | 69.95 feet to a nail in concrete; |
| 26. | 249° 10' 30" | 95.98 feet to a nail in concrete; |
| 27. | 253° 08' 30" | 55.43 feet to a nail in concrete; |
| 28. | 246° 33' 30" | 102.12 feet to a nail in concrete; |
| 29. | 251° 09' | 106.86 feet to a nail in concrete; |
| 30. | 256° 04' 30" | 75.94 feet to a nail in concrete; |
| 31. | 253° 30' 30" | 53.85 feet along stonewall, along Grant 3965 to W.M. Kalaiwaa to a cross (+) cut on south face of stonewall (found); |
| 32. | 253° 06' 30" | 266.02 feet along Grant 3924 to P. Peahi to a nail in concrete; |




L.C. Aw. 8608

33. 320° 30' 177.42 feet along R.P. 5123, L.C. Aw. 10950 to
Waiwaiole to the point of beginning and
containing an area of 3.357 Acres.

June 3, 1988
Hilo, Hawaii

ISLAND SURVEY, INC.

TMK: 7-4-04:35 portion


Nobuchika Santo
Registered Land Surveyor 1360-S

