Harry Kim Mayor

West Hawai'i Office 74-5044 Ane Keohokalole Hwy Kailua-Kona, Hawai'i 96740 Phone (808) 323-4770 Fax (808) 327-3563

February 1, 2017

Roger V. Meeker, Manager Pu'u Hue Ranch, LLC RR2 Box 3964 Ka poho, HI 96778

Dear Mr. Meeker:

### SUBJECT:VARIANCE DECISION - VAR-16-000400Applicant:ROGER V. MEEKER, MANAGEROwners:PU'U HUE RANCH, LLCRequest:Variance from Chapter 23, Subdivisions, Article 6, Division<br/>2, Improvements Required, Section 23-84, Water SupplyTax Map Key:5-7-001:017 (SUB-16-001628)

Upon review of your variance application, the Planning Director certifies the **approval** of Variance VAR-16-000400 subject to variance conditions. The variance grants relief for SUB-16-001628 from constructing minimum County dedicable water supply system improvements for the four (4) lots as required by Hawai'i County Code (HCC), Chapter 23 (Subdivisions).

The variance is from the proposed subdivision's minimum requirements pursuant to HCC, Chapter 23 (Subdivisions), Article 6, Division 2, Improvements Required, Section 23-84, Water Supply, (1)(2).

#### **BACKGROUND**

- 1. **Location.** The referenced property, Lot 1, Being Portions of Grant 2054 & Grant 2502, containing approximately 83.007 acres, is situated in Ka ipu ha'a, North Kohala, Hawai'i.
- 2. **County Zoning.** Agricultural, 20 acres minimum building site area (A20a).
- 3. **State Land Use.** Agricultural (A).

www.cohplanningdept.com

Hawai'i County is an Equal Opportunity Provider and Employer

planning@hawaiicounty.gov

Michael Yee Director

Daryn Arai Deputy Director

East Hawai<sup>4</sup>i Office 101 Pauahi Street, Suite 3 Hilo, Hawai<sup>4</sup>i 96720 Phone (808) 961-8288 Fax (808) 961-8742



County of Hawai'i PLANNING DEPARTMENT Roger V. Meeker, Manager Pu'u Hue Ranch, LLC Page 2 February 1, 2017

- 4. **General Plan.** Land Use Pattern Allocation Guide (LUPAG) map designates the property as Important Agricultural Lands (ial).
- 5. **Subdivision Code Requirements.** The subdivision code requires that subdivisions be served by a water system meeting the minimum requirements of the County Department of Water Supply (DWS) and be provided with water mains and fire hydrants installed to and within the subdivision in accordance with the rules and regulations of the DWS.
- 6. **Subdivision Request/PPM.** Subdivision application SUB-16-001628 was submitted to subdivide the subject TMK property into 4 lots. Further action on the subdivision application has been deferred pursuant to letter dated October 17, 2016 in the subdivision file.
- 7. **Variance Application.** The variance request from water supply improvements for the four (4) lots was acknowledged by Planning Department letter dated December 16, 2016. This variance application includes background history and circumstances and information regarding the pending subdivision application.
- 8. Variance Application (VAR-16-000400) Agency Comments and Requirements.
  - a. State of Hawai'i-Department of Health (DOH): See attached memorandum dated December 20, 2016 **(Exhibit A).**
  - b. County of Hawai'i Fire Department (HFD): See attached memorandum dated December 22, 2016 **(Exhibit B).**
  - c. Department of Water Supply (DWS): See attached memoranda dated January 5, 2017 **(Exhibit C)**. We have also attached their comments in response to the subdivision application **(Exhibit D)**.
  - d. No other agency comments were solicited and none were received.
- 9. **Notice to Surrounding Owners/Posted Sign.** The applicant submitted evidence, dated January 10, 2017, regarding the posting of a public notification sign on the subject property pursuant to Section 23-17(c) of the Hawai'i County Code (HCC). A picture of the posted sign was also submitted. The evidence also indicates that a notice of the application was sent to the surrounding property owners as required by Section 23-17(a).

Roger V. Meeker, Manager Pu'u Hue Ranch, LLC Page 3 February 1, 2017

10. **Comments from Surrounding Property Owners or Public.** There were no written comments on this application received from the surrounding property owners or the public.

#### **ANALYSIS OF GROUNDS FOR VARIANCE**

No variance will be granted unless it is found that:

(a) There are special or unusual circumstances applying to the subject real property which exist either to a degree which deprives the owner or applicant of substantial property rights that would otherwise be available or to a degree which obviously interferes with the best use or manner of development of that property.

The Variance application meets criterion (a) for the following reasons(s):

The subdivision request is for four (4) lots in keeping with the existing A20a zoning. Although a dedicable water system is a requirement of the code, the subject property is not able to be supported by the present service facilities of the existing DWS system and it would be unreasonable to expect the owners to construct the required service upgrades to serve the four (4) lots. Therefore, in lieu of constructing water system improvements to either extend/upgrade the DWS facilities or provide a private water system to DWS standards for the pending 4-lot subdivision, a more reasonable alternative can be allowed through Rule 22, Water Variance.

The above special and unusual circumstances would deprive the applicant from developing this property and interferes with the best use of this property.

Therefore, for this four (4) lot subdivision, the best use and manner of the development allows for individual rain water catchment system in keeping with the large lot, agricultural character of the area.

#### (b) There are no other reasonable alternatives that would resolve the difficulty.

The Variance application meets criterion (b) for the following reasons(s):

The DWS has indicated that the property is not served by water services at this time. Constructing water system improvements to either extend/upgrade the

Roger V. Meeker, Manager Pu'u Hue Ranch, LLC Page 4 February 1, 2017

DWS facilities or provide a private water system to DWS standards for the pending 4-lot subdivision would be placing excessive demands upon the applicant because of the extensive improvements and additions required to the existing DWS water system facilities. At an elevation of approximately 1,900 feet above sea level, the drilling of wells and construction of other water system improvements to DWS standards would also be unreasonable for a four (4) lot subdivision.

#### (c) The variance will be consistent with the general purpose of the district, the intent and purpose of this chapter, and the County general plan and will not be materially detrimental to the public welfare or cause substantial, adverse impact to an area's character or to adjoining properties.

The Variance application meets criterion (c) for the following reasons(s):

Given that there is adequate rainfall (approximately 60 inches to 80 inches of rainfall annually) to support individual water catchment for the four lots, the granting of this variance would be consistent with the general purpose of the district. Water catchment is consistent with the intent of the policies of the general plan in that it will further farming opportunities in this agricultural area. Water catchment will not be materially detrimental to the public welfare as it serves only private parties.

Subject to conditions, granting of the variance will not cause substantial, adverse impact to the area's character or to adjoining properties. The collection of rainwater could help to reduce runoff and may be a benefit to the surrounding area.

Given that the subject area receives sufficient annual rainfall, a water variance would be consistent with the general purpose of the zoning district and the intents and purposes of the Zoning Code, Subdivision Code and the Hawai'i County General Plan.

#### **DETERMINATION-VARIANCE CONDITIONS**

The variance to permit the proposed 4-lot subdivision of the subject TMK property without providing dedicable water system improvements meeting DWS standards is hereby **approved** subject to the following variance conditions:

1. The applicant, owners, their assigns, or successors shall be responsible for complying with all stated conditions of approval.

Roger V. Meeker, Manager Pu'u Hue Ranch, LLC Page 5 February 1, 2017

- 2. Should the Council adopt a Unified Impact Fees Ordinance setting forth criteria for the imposition of exactions or the assessment of impact fees, conditions included herein shall be credited towards the requirements of the Unified Impact Fees Ordinance.
- 3. The owners, their assigns, or successors shall file a written agreement document with the Planning Department within one (1) year from the issuance of tentative subdivision approval. This written agreement shall contain deed language, being covenants, conditions, and restrictions affecting the lots created by the proposed subdivision which are not serviced by a County dedicable public water system.

The agreement shall be duly recorded at the State of Hawai'i Bureau of Conveyances by and at the cost and expense of the owners. A copy of the recorded document shall be supplied to the Planning Department for our files.

In the event that there are any amendments or changes to the subdivision after the agreement is signed, the applicant shall be responsible for informing the County Planning Department of such amendments or changes so that the agreement can be amended concomitantly.

Further, the recorded agreement shall be binding upon the owner(s), their successors or assigns and shall be incorporated as an exhibit and made part of each agreement of sale, deed, lease, or similar documents affecting the title of the existing property or approved subdivided lots.

- 4. The subdivider and all grantees, successors, and assigns acknowledge that the parcels were created by a variance from the normal subdivision requirements of Hawai'i County, and that there are no longer any special or unusual circumstances applying to the property, and hence, no grounds exist or will exist for another variance from the Subdivision Code to permit further subdivision of the properties unless County dedicable public water system requirements and other requirements of HCC Chapter 23, Subdivisions, are met.
- 5. The owners, grantees, successors, and assigns agree and accept the fact that a County dedicable public water system will not be extended to serve the lots within proposed subdivision SUB-16-001628.
- 6. The owners, grantees, successors, and assigns agree and accept the fact that the County will not bear the responsibility of supplying public water to the subdivided lots. No

Roger V. Meeker, Manager Pu'u Hue Ranch, LLC Page 6 February 1, 2017

further subdivision of the lots will be permitted unless County dedicable public water system requirements and other requirements of HCC Chapter 23, Subdivisions, are met.

- 7. No condominium property regime will be allowed, nor will an Ohana Dwelling Unit be permitted or allowed.
- 8. Any dwelling constructed on any created lot not served by the DWS shall be provided with and maintain a private rainwater catchment system which includes a minimum 6,000-gallon water storage capacity for domestic consumption or potable uses. This private water storage system shall adhere to the University of Hawai'i's College of Tropical Agriculture and Human Resources' "Guidelines on Rainwater Catchment Systems for Hawai'i" as well as the DOH requirements related to water testing and water purifying devices.
- 9. In addition to the 6,000-gallon water storage capacity for domestic consumption or potable uses, each permitted dwelling on a lot not served by the DWS shall also be provided with a minimum 3,000 gallon water storage capacity dedicated for firefighting and emergency purposes. The location and capacity of the emergency water supply system, including the necessary compatible fire apparatus connector system and access routes shall meet with the approval of the HFD.

The HFD also advises, as a precautionary measure for other uninhabited structures, that consideration be given to the provision of a similar water storage system for firefighting and emergency purposes.

- 10. In the event that the County notifies the owner(s) of the lot(s) created that the County water system has been upgraded or an improvement district initiated to enable service to the lots, the owner(s) of the lots shall participate in such improvement district or shall pay their pro-rata share of the upgrade and installation of laterals, as determined by the DWS.
- 11. The pending subdivision application's (SUB-16-001628) final plat map shall meet all the requirements of the Hawai'i County Zoning Code and the Subdivision Code that are not covered by this variance.
- 12. The subdivider, owner(s), their assigns or successors shall pay any outstanding real property taxes and comply with all other applicable State statutes and County ordinances pertaining to building improvements and land use.

Roger V. Meeker, Manager Pu'u Hue Ranch, LLC Page 7 February 1, 2017

Should any of the foregoing conditions not be complied with, the Planning Director may proceed to declare this Variance Permit null and void.

Sincerely,

MICHAEL YEE

**Planning Director** 

JRH:nci

\\COH33\planning\public\Admin Permits Division\Variance\2016\VAR-16-000400 Puu Hue Water\APVL.docx

Encls: **Agency Comments** 

CC:

**DWS-Engineering Branch** HFD R. Newlon NKCPD (via email) SUB-16-001628

Robert T. Shirai, LPLS Island Survey, Inc. P.O. Box 4215 Hilo, HI 96720

cc w/encls: G. Bailado, GIS Section (via email)

to existing public water systems must receive construction plans approval by the Director prior to all new public water system sources be approved by the Director of I lealth (Director) prior to its alternative control measures which could be implemented to reduce or eliminate the potential for system in proximity to an existing potable water system to meet irrigation or other needs must be identified in the Hawai'i Source Water Assessment Plan) within the source water protection area pressure principle backflow prevention devices to avoid contaminating the potable water supply water protection plan for that source and activities which will take place to protect the source of carefully design and operate these systems to prevent the cross-connection of these systems and Further, all non-potable spigots and irrigated areas should be clearly labeled with warning signs use. Such approval is based primarily upon the submission of a satisfactory engineering report Director for this submittal or additional tests required upon his or her review of the information All sources of public water system sources must undergo a source water assessment which will contamination, including treatment of the water source. In addition, water quality analyses for delineate a source water protection area. This process is preliminary to the creation of a source Projects proposing to develop new public water systems or proposing substantial modifications All public water systems must be operated by certified distribution system and water treatment plant operators as defined by IIAR 11-25 titled, "Rules Pertaining to Certification of Public prevent the possibility of backflow of water from the non-potable system to the potable system. construction of the proposed system or modification in accordance with HAR 11-20-30, titled to prevent the inadvertent consumption on non-potable water. Compliance with HAR Chapter compliance with all drinking water standards. Additional parameters may be required by the activities that will be implemented to prevent or reduce the potential for contamination of the distribution systems of public water systems. The approval authority for projects owned and operated by a County Board or Department of Water or Water Supply has been delegated to The two (2) systems must be clearly labeled and physically separated by air gaps or reduced "New and Modified Public Water Systems". These projects include treatment, storage and All projects which propose the use of dual water systems or the use of a non-potable water In addition backflow devices must be tested periodically to assure their proper operation. The engineering report must identify all potential sources of contamination and evaluate all regulated contaminants, performed by a laboratory certified by the State Laboratories of an existing source of water for a public water supply should address this potential and All projects which propose the establishment of a potentially contaminating activity (as Division of the State of Hawaii, must be submitted as part of the report to demonstrate 1-21, titled Cross-Connection and Backflow Control is also required. which addresses the requirements specified in HAR 11-20-29. Water System Operators" drinking water source. Michael Yee December 20, 2016 drinking water. Page 2 of 3 submitted. hem. 2016 1150 21 VIRGINIA PRESSLER, M.D. DIRECTOR OF HEALTH 20), and titled "Rules Relating to Public Water Systems". All public water systems are regulated and Evaluation." This requirement involves demonstration that the system will have satisfactory litle 11. Chapter 20. Recommend the subdivision lots be connected to an existing public water Projects that propose development of new sources of potable water serving or proposed to serve a public water system must comply with the terms of HAR 11-20-29. This section requires that Public Water Systems: The Department of Health's Safe Drinking Water Branch authority on by the Department of Health and shall be in compliance with the Hawaii Administrative Rules. requirements prior to their establishment, per HAR 11-20-29.5, titled "Capacity Demonstration 17 regulations define a public water system as a system that serves 25 or more individuals at least Irinking water quality is based on the definition of a "public water system." Federal and state operators are required to comply with Hawaii Administrative Rules, Chapter 11-20 (HAR 11echnical. managerial and financial capacity to enable the system to comply with safe drinking 60 days per year or has at least 15 service connections. All public water system owners and Variance from Chapter 23. Subdivision. Article 6. Division 2. contaminations in private water systems have identified the need for self monitoring. The Department of Health does not support the use of these private rain catchment systems for All new public water systems are required to demonstrate and meet minimum capacity Improvements Required, Section 23-84, Water Supply Concerns on water quality for lead. copper. algae and microbiological and chemical drinking purposes since the quality may not meet potable water standards. ROGER V. MEEKER, MANAGER DEPARTMENT OF HEALTH P 0 BOX 916 HILO, HAWAII 96721-0916 5-7-001:017 (SUB-16-001628) Eric Honda () District Environmental Health Program Chief STATE OF HAWAII Application: VARIANCE VAR-16-000400 PUUHUE RANCH LLC Planning Director, County of Hawaii EXHIBIT December 20, 2016 water standards and requirements. Mr. Michael Yee Applicant: Owners: Request: TMK: MEMORANDUM DAVID Y. IGE GOVERNOR OF HAWAII SUBJECT: DATE FROM: svstem.

10

A

Durren J. Rouario Parcento Remarka A. Vatorino	County of Matuai'i HAWAI'I FIRE DEPARTMENT 25 Awad Stere - Sair 2010 - HIM, Hawei 19720 (000) 932-2900 - Fix (000) 932-2928	HAEL VEF. PLANNING DIRECTOR	DARREN J. ROSARIO, FIRE CHIEF	VARIANCE – VAR 16-000400 Applicant: Roger V. Meeker, Manager Owners: Pu'u Hue Ranch, LLC Request: Variance from Chapter 23, Subdivisions, Article 6, Division 2 Improvements Required, Section 23-84, Water Supply Tax Map Key: 5-7-001:017 (SUB 16-001628)	In regards to the above-mentioned Variance application, the following shall be in accordance:	NFPA 1, UNIFORM FIRE CODE, 2006 EDITION Note: Hawa'' State Fire Code. National Fire Protection Association 2006 version, with County of Hawaii amendments. County amendments are identified with a preceding " $C^{-n}$ of the reference code.	Chapter 18 Fire Department Access and Water Supply	18.1 General. Fire department access and water supplies shall comply with this chapter.	For occupancies of an especially hazardous nature, or where special hazards exist in addition to the normal hazard of the occupancy, or where access for fire apparatus is unduly difficult, or areas where there is an inadequate fire flow, or inadequate fire hydrant spacing, and the AHJ may require additional safeguards including, but not limited to, additional fire appliance units, more than one type of appliance, or special systems suitable for the protection of the hazard involved.		18.1.1.1 Fire Apparatus Access. Plans for fire apparatus access roads shall be submitted to the fire department for review and approval prior to construction.	18.1.1.1.2 Fire Hydrant Systems. Plans and specifications for fire hydrant systems shall be submitted to the fire department for review and approval prior to construction.	EXHIBIT B 109075
Harry Kim Mape		December 22, 2016 TO: MIC	:W	SUBJECT: VA App Own Reg	In regards to the ab	NFPA 1, UNIFOJ Note: Hawai'i Stat of Hawaii amendm reference code.	Chapter 18 Fire De	18.1 General. Fire	For occupancies of the normal hazard, areas where there i may require addition more than one type involved.	18.1.1 Plans.	18.1.1.1 Fire Appr fire department for	18.1.1.2 Fire Hydr submitted to the fit	
Michael Yee December 20, 2016 Page 3 of 3	For further information concerning the application of capacity, new source approval, operator certification, source water assessment, backflow/cross-connection prevention or other public water system programs, please contact the SDWB at 386-4258.									A DAMAGE A D			

Michael Yee December 22, 2016 Page 2 C~ 18.1.1.2.1 Fire Hydrant use and Restrictions. No unauthorized person shall use or operate any Fire hydrant unless such person first secures permission or a permit from the owner or representative of the department, or company that owns or govers that water apply or system. Exception: Fire Department personnel conducting firefighting operations, hydrant testing, aydem maintenance, and the flushing and acceptance of hydrants witnessed by Fire Prevention Bueau persond.

### 18.2 Fire Department Access.

18.2.1 Fire department access and fire department access roads shall be provided and maintained in accordance with Section 18.2.

### 18.2.2\* Access to Structures or Areas.

18.2.2.1 Access Box(es). The AHJ shall have the authority to require an access box(es) to be installed in an accessible location where access to or within a structure or area is difficult because of security. 18.2.2.2 Access to Gated Subdivisions or Developments. The AHJ shall have the authority to require fire department access be provided to gated subdivisions or developments through the use of an approved device or system.

18.2.2.3 Access Maintenance. The owner or occupant of a structure or area, with required fire department access as specified in 18.2.2.1 or 18.2.2.2, shall notify the AHJ when the access is modified in a manner that could prevent fire department access.

18.2.3 Fire Department Access Roads. (\*may be referred as FDAR)

18.2.3.1 Required Access.

18.2.3.1.1 Approved fire department access roads shall be provided for every facility, building, or portion of a building hereafter constructed or relocated. 18.2.3.1.2 Fire Department access roads shall consist of roadways, fire lanes, parking lots lanes, or a combination thereof. **18.2.3.1.3\*** When not more than two one- and two-family dwellings or private garages, carports, sheds, agricultural buildings, and detached buildings or structures 400 $H^3$  (37 m<sup>3</sup>) or less are present, the requirements of 18.2.3.1 through 18.2.3.2.1 shall be permitted to be modified by the AHI.

Michael Yee December 22, 2016 Page 3 18.2.3.1.4 When fire department access roads cannot be installed due to location on property, topography, waterways, nonnegotiable grades, or other similar conditions, the AHJ shall be authorized to require additional fire protection features.

### 18.2.3.2 Access to Building.

**18.2.3.2.1** A fire department access road shall extend to within in 50 ft (15 m) of at least one exterior door that can be opened from the outside that provides access to the interior of the building. Exception: 1 and 2 single-family dwellings.

**18.2.3.2.1.1** When buildings are protected throughout with an approved automatic sprinkler system that is installed in accordance with NFPA 13, NFPA 13D, or NFPA 13R, the distance in 18.2.3.2.1 shall be permitted to be increased to 300 feet.

**18.2.3.2.2** Fire department access roads shall be provided such that any portion of the facility or any portion of an exterior wall of the first story of the building is located not more than 150 ft (46 m) from fire department access roads as measured by an approved route around the exterior of the building or facility.

**18.2.3.2.1** When buildings are protected throughout with an approved automatic sprinkler system that is installed in accordance with NFPA 13, NFPA 13D, or NFPA 13R, the distance in 18.2.3.2.2 shall be permitted to be increased to 450 ft (137 m).

18.2.3.3 Multiple Access Roads. More than one fire department access road shall be provided when it is determined by the AHJ that access by a single road could be impaired by vehicle congestion, condition of terrain, climatic conditions, or other factors that could limit access.

18.2.3.4 Specifications.

18.2.3.4.1 Dimensions.

C~ 18.2.3.4.1.1 FDAR shall have an unobstructed width of not less than 20ft with an approved turn around area if the FDAR exceeds 150 feet. Exception: FDAR for one and two family dwellings shall have an unobstructed width of not less than 15 feet, with an area of not less than 20 feet wide within 150 feet of the structure being protected. An approved turn around area shall be provided if the FDAR exceeds 250 feet.

C~ 18.2.3.4.1.2 FDAR shall have an unobstructed vertical clearance of not less then 13ft 6 in.

C~ 18.2.3.4.1.2.1 Vertical clearances may be increased or reduced by the AHJ, provided such increase or reduction does not impair access by the fire apparatus, and approved signs are installed and maintained indicating such approved changes.

Page 4	December 22, 2016 Page 5
18.2.3.4.1.2.2 Vertical clearances shall be increased when vertical clearances or widths are not adequate to accommodate fire apparatus.	18.2.3.4.7 Traffic Calming Devices. The design and use of traffic calming devices shall be approved the AHJ.
C- 18.2.3.4.2 Surface. Fire department access roads and bridges shall be designed and maintained to support the imposed loads (25 Tons) of the fire apparatus. Such FDAR and shall be comprised of an all-weather ciriving surface.	<ol> <li>18.2.3.5 Marking of Fire Apparatus Access Road.</li> <li>18.2.3.5.1 Where required by the AHJ, approved signs or other approved notices shall be</li> </ol>
18.2.3.4.3 Turning Radius.	provided and maintained to identify fire department access roads or to prohibit the obstruction thereof of both.
C- 18.2.3.4.3.1 Fire department access roads shall have a minimum inside turning radius of 30 feet, and a minimum outside turning radius of 60 feet.	18.2.3.5.2 A marked fire apparatus access road shall also be known as a fire lane.
18.2.3.4.3.2 Turns in fire department access road shall maintain the minimum road width.	18.2.4* Obstruction and Control of Fire Department Access Road.
18.2.3.4.4 Dead Ends. Dead-end fire department access roads in excess of 150 ft (46 m) in length shall be novided with anorowed provisions for the fire anoratabus to turn around.	18.2.4.1 General. 18.2.4.1.1 The remuted width of a fire domartment access mad shall not be obstructed in one
	mamer, including by the parking of vehicles.
18.2.3.4.5.1. When a bridge is required to be used as part of a fire department access road, it shall be constructed and maintained in accordance with county requirements.	18.2.4.1.2 Minimum required widths and clearances established under 18.2.3.4 shall be maintained at all times.
18.2.3.4.5.2 The bridge shall be designed for a live load sufficient to carry the imposed loads of fire apparatus.	18.2.4.1.3* Facilities and structures shall be maintained in a manner that does not impair or impede accessibility for fire department operations.
18.2.3.4.5.3 Vehicle load limits shall be posted at both entrances to bridges where required by the AHJ.	18.2.4.1.4 Entrances to fire departments access roads that have been closed with gates and barriers in accordance with 18.2.4.2.1 shall not be obstructed by parked vehicles.
18.2.3.4.6 Grude.	18.2.4.2 Closure of Accessways.
C-18.2.3.4.6.1 The maximum gradient of a Fire department access road shall not exceed 12 percent for upwed surfaces and 15 percent for paved surfaces. In areas of the FDAR where a Fire anomary consult consorts to a Fire Mortan to Fire American Demonstruction the maximum	18.2.4.2.1 The AHJ shall be authorized to require the installation and maintenance of gates or other approved barricades across roads, trails, or other accessways not including public streets, alleys, or highways.
are appeared your control to a rate to up and or the coperation control of the maximum gradient of such area(s) shall not exceed 10 percent.	18.2.4.2.2 Where required, gates and barricades shall be secured in an approved manner.
<b>18.2.3.4.6.2*</b> The angle of approach and departure for any means of fire department access road shall not exceed 1 ft drop in $20$ ft ( $0.3$ m drop in 6 m) or the design limitations of the fire apparatus of the fire department, and shall be subject to approval by the AHJ.	18.2.4.2.3 Roads, trails, and other access ways that have been closed and obstructed in the manner prescribed by 18.2.4.2.1 shall not be trespassed upon or used unless authorized by the owner and the AHJ.
18.2.3.4.6.3 Fire department access roads connecting to roadways shall be provided with curb outs extending at least 2 ft (0.61 m) beyond each edge of the fire lane.	<b>18.2.4.2.4</b> Public officers acting within their scope of duty shall be permitted to access restricted property identified in 18.2.4.2.1.

Michael Yee December 22, 2016 Page 6 18.2.4.2.5 Locks, gates, doors, barricades, chains, enclosures, signs, tags, or seals that have been installed by the fire department or by its order or under its control shall not be removed, unlocked, destroyed, tampered with, or otherwise vandalized in any manner.

# 18.3 Water Supplies and Fire Hydrants

facility or building is in excess of 150 feet (45 720 mm) from a water supply on a fire apparatus access road, as measured by an approved route around the exterior of the facility or building, on-site fire hydrants and mains capable of supplying the required fire flow shall be provided when thereof, are hereafter constructed, or moved into or within the county. When any portion of the 18.3.1\* A water supply approved by the county, capable of supplying the required fire flow for fire protection shall be provided to all premises upon which facilities or buildings, or portions required by the AHJ. For on-site fire hydrant requirements see section 18.3.3.

#### **EXCEPTIONS:**

- When facilities or buildings, or portions thereof, are completely protected with an approved automatic fire sprinkler system the provisions of section 18.3.1 may be modified by the AHJ.
- conditions, the AHJ may require additional fire protection as specified in section 18.3.2 When water supply requirements cannot be installed due to topography or other as amended in the code. ci
- When there are not more than two dwellings, or two private garage, carports, sheds and agricultural. Occupancies, the requirements of section 18.3.1 may be modified by AHJ. 3

pressure tanks, elevated tanks, fire department tanker shuttles, or other approved systems capable 18.3.2\* Where no adequate or reliable water distribution system exists, approved reservoirs, of providing the required fire flow shall be permitted.

18.3.3\* The location, number and type of fire hydrants connected to a water supply capable of delivering the required fire flow shall be provided on a fire apparatus access road on the site of the premises or both, in accordance with the appropriate county water requirements. 18.3.4 Fire Hydrants and connections to other approved water supplies shall be accessible to the fire department. 18.3.5 Private water supply systems shall be tested and maintained in accordance with NFPA 25 or county requirements as determined by the AHJ.

18.3.6 Where required by the AHJ, fire hydrants subject to vehicular damage shall be protected unless located within a public right of way.

Michael Yee December 22, 2016 Page 7

to service. Owners of private property required to have hydrants shall maintain hydrant records 18.3.7 The AHJ shall be notified whenever any fire hydrant is placed out of service or returned of approval, testing, and maintenance, in accordance with the respective county water requirements. Records shall be made available for review by the AHJ upon request.

C~18.3.8 Minimum water supply for buildings that do not meet the minimum County water standards: Buildings up to 2000 square feet, shall have a minimum of 3,000 gallons of water available for Firefighting. Buildings 2001- 3000 square feet, shall have a minimum of 6,000 gallons of water available for Firefighting. Buildings, 3001- 6000 square feet, shall have a minimum of 12,000 gallons of water available for

Firefighting.

Buildings, greater than 6000 square feet, shall meet the minimum County water and fire flow

requirements.

Multiple story buildings shall multiply the square feet by the amount of stories when determining the minimum water supply.

Commercial buildings requiring a minimum fire flow of 2000gpm per the Department of Water standards shall double the minimum water supply reserved for firefighting.

Fire Department Connections (FDC) to alternative water supplies shall comply with 18.3.8 (1)-(6) of this code.

# NOTE: In that water condimentarytens are being will as a minup of weber waydy for firefighting, ands systems shall most the Millining waydbungets:

domestic use shall not be capable of being drawn from the water reserved for firefighting; 1) In that a single water tank is used for both domestic and firefighting water, the water for

2) Minimum pipe diameter sizes from the water supply to the Fire Department Connection

(FDC) shall be as follows:

a) 4" for C900 PVC pipe;
b) 4" for C906 PE pipe;
c) 3" for ductile Iron;
d) 3' for galvanized steel.

Michael Yce December 22, 2016 Page 8 3) The Fire Department Connection (FDC) shall:

a) be made of galvanized steel;
 b) have a gated valve with 2-1/2 inch, National Standard Thread male fitting and cap;
 c) be located between 8 ft and 16 ft from the Fire department access. The location shall be

approved by the AHJ; d) not be located less than 24 inches, and no higher than 36 inches from finish grade, as

e) be secure and capable of withstanding drafting operations. Engineered stamped plans measured from the center of the FDC orifice;

may be required;

f) not be located more than 150 feet of the most remote part, but not less than 20 feet, of the structure being protected;

g) also comply with section 13.1.3 and 18.2.3.4.6.1 of this code.

FDC. Each FDC shall be independent of each other, with each FDC being capable of flowing 500gpm by engineered design standards. The second FDC shall be located in an area approved by the AHJ with the idea of multiple Fire apparatus' conducting drafting operations 4) Commercial buildings requiring a fire flow of 2000gpm shall be provided with a second at once, in mind.

5) Inspection and maintenance shall be in accordance to NFPA 25.

6) The owner or lessee of the property shall be responsible for maintaining the water level, quality, and appurtenances of the system.

## **EXCEPTIONS TO SECTION 18.3.8:**

1) Agricultural buildings, storage sheds, and shade houses with no combustible or equipment storage. 2) Buildings less than 800 square feet in size that meets the minimum Fire Department Access Road requirements.

garages 800 to 2000 square feet in size, and meets the minimum Fire Department Access Road requirements, the distance to the Fire Department Connection may be increased to 1000 3) For one and two family dwellings, agricultural buildings, storage sheds, and detached feet. 4) For one and two family dwellings, agricultural buildings, and storage sheds greater than 2000square feet, but less than 3000 square feet and meets the minimum Fire Department Access Road requirements, the distance to the Fire Department Connection may be increased to 500 feet.

Michael Yee December 22, 2016 Page 9 5) For buildings with an approved automatic sprinkler system, the minimum water supply required may be modified. If there are any questions regarding these requirements, please contact the Fire Prevention Bureau at (808) 323-4761.

0.2.

DARREN J. ROSARIO Fire Chief

CB/ds

DEPARTMENT OF WATER SUPPLY · COUNTY OF HAWAI'I	October 12, 2016	TO: Mr. Duane Kanuha, Director Planning Department FROM: Keith K. Okamoto, Manager-Chief Engineer	SUBJECT: Preliminary Plat Map and Defer Action Subdivision Application No. SUB-16-001628 Subdivider: Pu'n Hue Ranch LLC Tax Map Key 5-7-001:017	We have reviewed the subject application for the proposed subdivision. Please be informed that the subject parcel is beyond the service limits of the Department's existing water system facilities. Therefore, the Department cannot support the proposed subdivision.	Extensive improvements and additions, including source, storage, transmission, booster J distribution facilities, must be constructed.	Should there be any questions, please contact Mr. Ryan Quitoriano of our Water Resources and Planning Branch at 961-8070, extension 256.	Sincerely yours,	domination .	Keith K. Okamoto, P.E. Manager-Chief Engineer	кQ:atg copy – Pu'u Hue Ranch LLC Mr. Robert Shirai, Island Survey, Inc.	EXHIBIT D Water, Our Most Precious Resource Ka Wai A Kâne De Department of Wane Supply is an Equal Opportung provider and amployee.	
DEPARTMENT OF WATER SUPPLY · COUNTY OF HAWAI'I 345 KEKUANAG'A STREET, SUITE 20 · HILO, HAWAI'I 96720 TELEPHONE (808) 961-8050 · FAX (808) 961-8657		eer Deer	We have reviewed the subject application No. SUB-16-001628 Subdivision Application No. SUB-16-001628 Tax Map Key 5-7-001:017 We have reviewed the subject application and our comments to you in our letter dated October 12,	2010, sun stant. Should there be any questions, please contact Mr. Ryan Quitoriano of our Water Resources and Planning Branch at 961-8070, extension 256.	Sincerely yours,	Comment	Keith K. Okamoto, P.E. Manager-Chief Engineer	RQ:dfg	copy – Pu'u Huc Ranch, LLC		EXHIBIT C 2 Mater, Our Most Precions Resource Ka Wai, A Kane The Department of Wave Supply is an Equal Opportunity provider, and employee	